## **NETWORK KEYBOARD**

MODEL: TB-K98A10-DP

## **Product pictures**



## **Key Features**

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Support up to 32 users and 4,000 devices
- Suitable for outdoor camera equipment, IP receiver and signal processor.

Specifications	
Joystick	3-axis, vector-solving, with twisting, return to-center head
Keyboard Connector	IP/Ethernet, RS232, RS485, RS422, USB
Keyboard Communication	Direct Mode, Network Mode
Direct Mode	Interface: RS232/RS485
	DVR Protocol: TBVISION/ONVIF
	Dome Protocol: TBVISION/PELCO-D/PELCO-P/PELCO-D1/PELCO-P/ONVIF, etc
Network Mode	Interface: RJ45 DVR/Network
	IP Address/Port/Protocol
Display	LCD 7" TFT 1024 × 600
Power Supply	Power adapter, input 100~214VAC 50Hz/60Hz, output DC12V/1000mA
Power Consumption	10W
Operating Conditions	-10 °C to 55 °C
Operating Humidity	5 to 90%



Email: sale@tbvision.net | Website: tbvision.net |