

NETWORK KEYBOARD

TB-KI0500

SECURING YOUR LIFE

Product Image



Key Features

- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Support up to 32 users and 4,000 devices

Specifications

| Technical Specifications | |
|--------------------------------|---|
| Joystick | 3-axis, vector-solving, with twisting, return to-center head |
| Keyboard Connector | RJ-45, RS232, RS485, RS422, USB |
| Keyboard Communication | Direct Mode, Network Mode Interface: RS232/RS485 |
| Direct Mode | DVR Protocol: VEILUX Dome Protocol: VEILUX/PELCO-D/PELCO-P/PELCO-D1/PELCO-P, etc |
| Network Mode | Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol |
| Display | LCD 7" TFT 1024 × 600 |
| Power Supply Power Consumption | Power adapter, input 100V~240V 50Hz/60Hz, output DC12V/1000mA 10W |
| Working Temperature | -10 °C to +55 °C (14 °F to 131 °F) |
| Working Humidity | 5% to 90% |

Specifications subject to change without notice.



TBVISION SECURITY

Address: 87, Jalan 20/7, Paramount Garden, 46300 Petaling Jaya, Malaysia

| Email : sale@tbvision.net | Website : tbvision.net |